

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Date of issue: 01/18/2018 Version: 1.0

SECTION 1: Identification**1.1. Identification**

Product form : Mixture
 Product name : Nissen SOLID PAINT MARKER - Low Corrosion
 Synonyms : Nissen SOLID PAINT MARKER Low Corrosion White, Low Corrosion Yellow, Low Corrosion Red, Low Corrosion Black

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Marking.
 Restrictions on use : No additional information available

1.3. Details of the supplier of the safety data sheet

LA-CO Industries, Inc.
 1201 Pratt Boulevard
 Elk Grove Village, IL. 60007-5746
 Phone: (847) 956-7600
 Fax: (847) 956-9885
 E-mail: customer_service@laco.com

1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****classification**

Skin corrosion/irritation Category 2 H315
 Serious eye damage/eye irritation Category 1 H318
 Hazardous to the aquatic environment - Chronic Hazard Category 3 H412

Full text of H statements : see section 16

2.2. Label elements**labeling**

Hazard pictograms :



GHS05

Signal word : Danger
 Hazard statements : H315 - Causes skin irritation
 H318 - Causes serious eye damage
 H412 - Harmful to aquatic life with long lasting effects
 Precautionary statements : P264 - Wash hands thoroughly after handling.
 P273 - Avoid release to the environment.
 P280 - Wear protective gloves, eye protection.
 P302+P352 - If on skin: Wash with plenty of water
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P310 - Immediately call a doctor
 P321 - Specific treatment (see First aid measures on this label)
 P332+P313 - If skin irritation occurs: Get medical advice/attention.
 P362+P364 - Take off contaminated clothing and wash it before reuse.
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

66.91% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

Nissen SOLID PAINT MARKER - Low Corrosion

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

66.91% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

66.91% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	classification
titanium dioxide	(CAS-No.) 13463-67-7	8.19 - 19.83	Carc. Not classified
Steamide MEA	(CAS-No.) 111-57-9	9.6 - 12.16	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411
Carbon black	(CAS-No.) 1333-86-4	0 - 9	Carc. 2, H351 (dust)
Methyl ester, soybean oil	(CAS-No.) 68919-53-9	3.74 - 5.65	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
ethyl lactate	(CAS-No.) 97-64-3	1.69 - 4.5	Flam. Liq. 3, H226 Eye Dam. 1, H318 STOT SE 3, H335
Ethyl acetate	(CAS-No.) 141-78-6	0.22 - 1.8	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Butyl acetate	(CAS-No.) 123-86-4	0.63 - 1.69	Flam. Liq. 3, H226 STOT SE 3, H336
2-aminoethanol	(CAS-No.) 141-43-5	0.5 - 0.6	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1B, H314 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
- First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after skin contact : Causes skin irritation.
- Symptoms/effects after eye contact : Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Burning produces irritating, toxic and noxious fumes.
- Explosion hazard : Product is not explosive.
- Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

Nissen SOLID PAINT MARKER - Low Corrosion

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin, eyes and clothing. Avoid creating or spreading dust.

6.1.1. For non-emergency personnel

Protective equipment : Refer to section 8.2.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Refer to section 8.2.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain and collect as any solid.

Methods for cleaning up : On land, sweep or shovel into suitable containers. Minimize generation of dust. Store away from other materials.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

Hygiene measures : Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Keep only in the original container.

Incompatible products : Strong oxidizers.

Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Nissen SOLID PAINT MARKER - Low Corrosion		
ACGIH	Not applicable	
OSHA	Not applicable	
ethyl lactate (97-64-3)		
ACGIH	Not applicable	
OSHA	Not applicable	
Ethyl acetate (141-78-6)		
ACGIH	ACGIH TWA (mg/m ³)	1440 mg/m ³
ACGIH	ACGIH TWA (ppm)	400 ppm
ACGIH	Remark (ACGIH)	URT & eye irr
OSHA	OSHA PEL (TWA) (mg/m ³)	1400 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	400 ppm
Canada (Quebec)	VEMP (mg/m ³)	1440 mg/m ³
Canada (Quebec)	VEMP (ppm)	400 ppm

Nissen SOLID PAINT MARKER - Low Corrosion

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Methyl ester, soybean oil (68919-53-9)		
ACGIH	Not applicable	
OSHA	Not applicable	
Butyl acetate (123-86-4)		
ACGIH	ACGIH TWA (mg/m ³)	713 mg/m ³
ACGIH	ACGIH TWA (ppm)	150 ppm
ACGIH	ACGIH STEL (mg/m ³)	950 mg/m ³
ACGIH	ACGIH STEL (ppm)	200 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
OSHA	OSHA PEL (TWA) (mg/m ³)	710 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	150 ppm
Canada (Quebec)	VECD (mg/m ³)	950 mg/m ³
Canada (Quebec)	VECD (ppm)	200 ppm
Canada (Quebec)	VEMP (mg/m ³)	713 mg/m ³
Canada (Quebec)	VEMP (ppm)	150 ppm
Stearmide MEA (111-57-9)		
ACGIH	Not applicable	
OSHA	Not applicable	
2-aminoethanol (141-43-5)		
ACGIH	ACGIH TWA (mg/m ³)	7.5 mg/m ³
ACGIH	ACGIH TWA (ppm)	3 ppm
ACGIH	ACGIH STEL (mg/m ³)	15 mg/m ³
ACGIH	ACGIH STEL (ppm)	6 ppm
ACGIH	Remark (ACGIH)	Eye & skin irr
OSHA	OSHA PEL (TWA) (mg/m ³)	6 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	3 ppm
Canada (Quebec)	VECD (mg/m ³)	15 mg/m ³
Canada (Quebec)	VECD (ppm)	6 ppm
Canada (Quebec)	VEMP (mg/m ³)	7.5 mg/m ³
Canada (Quebec)	VEMP (ppm)	3 ppm
titanium dioxide (13463-67-7)		
ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³
ACGIH	Remark (ACGIH)	LRT irr; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans: The agent is carcinogenic in experimental animals at a relatively high dose, by route(s) of administration, at site(s), of histologic type(s), or by mechanism(s) that may not be relevant to worker exposure. Available epidemiologic studies do not confirm an increased risk of cancer in exposed humans. Available evidence does not suggest that the agent is likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure)
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³
Canada (Quebec)	VEMP (mg/m ³)	10 mg/m ³
Canada (Quebec)	Notations and remarks	(la poussière totale), (note1)
Carbon black (1333-86-4)		
ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³
ACGIH	Remark (ACGIH)	Bronchitis
OSHA	OSHA PEL (TWA) (mg/m ³)	3.5 mg/m ³

Nissen SOLID PAINT MARKER - Low Corrosion

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Carbon black (1333-86-4)

Canada (Quebec)	VEMP (mg/m ³)	10 mg/m ³ (Fibres de carbone et de graphite; Poussière totale) 5 mg/m ³ (Fibres de carbone et de graphite; Poussière respirable) 3.5 mg/m ³
-----------------	---------------------------	--

8.2. Exposure controls

Appropriate engineering controls	: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide local exhaust or general room ventilation.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear suitable gloves resistant to chemical penetration.
Eye protection	: Chemical goggles or safety glasses.
Respiratory protection	: None under normal use.
Environmental exposure controls	: Prevent leakage or spillage.
Other information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: A solid crayon-like marker.
Color	: Variable
Odor	: odorless
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

Nissen SOLID PAINT MARKER - Low Corrosion

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Inhalation; Skin and eye contact

Acute toxicity : Not classified

ethyl lactate (97-64-3)	
LD50 oral rat	> 4090 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5400 mg/m ³

Ethyl acetate (141-78-6)	
LD50 oral rat	5620 mg/kg
LD50 dermal rabbit	> 20000 mg/kg
LC50 inhalation rat (mg/l)	> 18 mg/l/4h
ATE US (oral)	5620 mg/kg body weight

Butyl acetate (123-86-4)	
LD50 oral rat	10760 mg/kg
LD50 dermal rabbit	> 14112 mg/kg
LC50 inhalation rat (mg/l)	> 21 mg/l/4h
ATE US (oral)	10760 mg/kg body weight

2-aminoethanol (141-43-5)	
LD50 oral rat	1515 mg/kg
LD50 dermal rabbit	1822 (1822 - 3451) mg/kg
LC50 inhalation rat (mg/l)	> 1.3 mg/l
ATE US (oral)	1515 mg/kg body weight
ATE US (dermal)	1822 mg/kg body weight
ATE US (dust, mist)	1.5 mg/l/4h

titanium dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg
LC50 inhalation rat (mg/l)	> 6.82 mg/l/4h

Carbon black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg
LC50 inhalation rat (mg/l)	> 4.6 mg/m ³ 4 h

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified.

Germ cell mutagenicity : Not classified

Based on available data, the classification criteria are not met

Carcinogenicity : Not classified.

titanium dioxide (13463-67-7)	
NOAEL (chronic,oral,animal/male,2 years)	5 mg/kg body weight rat
IARC group	2B - Possibly carcinogenic to humans

Carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans, Inhalation of dust

Reproductive toxicity : Not classified

Based on available data, the classification criteria are not met

Nissen SOLID PAINT MARKER - Low Corrosion

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye damage.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Harmful to aquatic life with long lasting effects.

Ethyl acetate (141-78-6)	
LC50 fish 1	220 mg/l
EC50 Daphnia 1	1200 mg/l
NOEC chronic fish	< 9.35 mg/l

Stearmide MEA (111-57-9)	
LC50 fish 1	31 mg/l 96 h read-across

2-aminoethanol (141-43-5)	
LC50 fish 1	165 mg/l 48 h
EC50 Daphnia 1	65 mg/l 48 h

12.2. Persistence and degradability

Nissen SOLID PAINT MARKER - Low Corrosion	
Persistence and degradability	May cause long-term adverse effects in the environment.

ethyl lactate (97-64-3)	
Persistence and degradability	Readily biodegradable.

Ethyl acetate (141-78-6)	
Persistence and degradability	Readily biodegradable.

Stearmide MEA (111-57-9)	
Biodegradation	69 % 28 d

2-aminoethanol (141-43-5)	
Persistence and degradability	Readily biodegradable.

Carbon black (1333-86-4)	
Persistence and degradability	Not readily biodegradable.

12.3. Bioaccumulative potential

Nissen SOLID PAINT MARKER - Low Corrosion	
Bioaccumulative potential	Not established.

Ethyl acetate (141-78-6)	
Bioaccumulative potential	Not expected to bioaccumulate.

Stearmide MEA (111-57-9)	
Log Pow	> 4.46

2-aminoethanol (141-43-5)	
Log Pow	-1.31

12.4. Mobility in soil

Nissen SOLID PAINT MARKER - Low Corrosion	
Ecology - soil	Not established.

12.5. Other adverse effects

Other information : Avoid release to the environment.

Nissen SOLID PAINT MARKER - Low Corrosion

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with US-DOT 49-CFR and the HMR / TDG / ADR / IMDG / ICAO / IATA

In accordance with DOT

Not applicable

Transportation of Dangerous Goods

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Ethyl acetate (141-78-6)

CERCLA RQ	5000 lb
-----------	---------

Butyl acetate (123-86-4)

CERCLA RQ	5000 lb
-----------	---------

15.2. International regulations No additional information available

National regulations

Nissen SOLID PAINT MARKER - Low Corrosion

All components are listed on the EEC inventory European Inventory of Existing Commercial Chemical Substances (EINECS).
All ingredients are listed in the Domestic Substances List (DSL).

15.3. US State regulations

Nissen SOLID PAINT MARKER - Low Corrosion

State or local regulations	The carbon black and titanium dioxide in this product are bound and are not respirable. California Prop. 65 warnings are not required.
----------------------------	---

ethyl lactate (97-64-3)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

Ethyl acetate (141-78-6)

U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - Pennsylvania - RTK (Right to Know) List

Butyl acetate (123-86-4)

U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Nissen SOLID PAINT MARKER - Low Corrosion

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

2-aminoethanol (141-43-5)

U.S. - New York - Right to Know List of Hazardous Substances
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Minnesota - Hazardous Substance List
U.S. - Washington - Permissible Exposure Limits - Carcinogens
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)

titanium dioxide (13463-67-7)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

Carbon black (1333-86-4)

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Data sources : ACGIH (American Conference of Government Industrial Hygienists).
European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.
Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.
National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.
OSHA 29CFR 1910.1200 Hazard Communication Standard.
TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

Other information : None.

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Abbreviations and acronyms:


ATE: Acute Toxicity Estimate
CAS (Chemical Abstracts Service) number
CLP: Classification, Labelling, Packaging.
EC50: Environmental Concentration associated with a response by 50% of the test population.
GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
LD50: Lethal Dose for 50% of the test population
OSHA: Occupational Safety & Health Administration
PBT: Persistent, Bioaccumulative, Toxic
TWA: Time Weighted Average
TSCA: Toxic Substances Control Act

Nissen SOLID PAINT MARKER - Low Corrosion

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

- NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
- NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
- NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



SDS Prepared by: The Redstone Group, LLC
6077 Frantz Rd.
Suite 206
Dublin, OH USA 43017
T 614-923-7472
www.redstonegrp.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product